

PRODUCT DESCRIPTION :

A high quality long oil alkyd gloss enamel with excellent resistant to weathering and mildew growth. It has very good gloss retention and light fastness.

RECOMMENDED USE :

It is most suitable for decoration and protection of both interior and exterior of all wooden, metal and masonry surface such as steel or concrete (with proper priming)

PHYSICAL DATA :

Colour	According to colour card		
Volume Solid (%)	60 $\pm$ 2	(ASTM D2697 Modified)	
Specific gravity	1.09 $\pm$ 0.05	Drying time @ 25 deg C	
Gloss	High gloss	Dry to touch	2 - 3 Hrs.
Surface	Ferrous surface	Curing time	48-72 hrs
Flash point	27 deg C		
Film thickness recommended	40-60 microns [D.F.T.]		
Theoretical coverage	15.00-10.00 sq.m / Litre.		

APPLICATION DATA :

Application method	Brush, Roller, or Airless Spray
Temperature	5 - 45 °C
Humidity	10 - 85 % R.H.
Thinning	Victor Thinner AAA 5-10 % by volume

SURFACE PREPARATION :

All surface must be dry and clean, free from rust millscale, dirt and oil that may cause the film defects.

RECOMMENDED SYSTEM :

Metal Surface

PRIMER	Neocoat Primer
TOP	Neogloss Enamel

Masonry Surface

PRIMER	Neocoat Masonry Sealer
TOP	Neogloss Enamel

STORAGE AND HANDLING :

Storage	The product must be store in well ventilated place protected from high temperature. Container must be kept tightly closed .
Handling	Handle with care . Stir well before use .
Packing	1 U.S. gallon , 5 U.S. gallon

HEALTH AND SAFETY :

Avoid contact with skin and eyes wear . Wear suitable protective clothing such as overalls during painting.
 Avoid skin contact . Spillage on skin should immediately be remove with soap and water.
 Eyes should be flushed with water and medical attention sought immediately.